



ANCHORING AND WEDGES FOR 1 TO 55-HOLE PLATES.

ANCHORING AND WEDGES

We distribute wedge holders and anchoring wedges for 12.7mm (0.5") and 15.24mm (0.6") strands. Plate distributions range from 2 to 55 holes (strands). Our products are certified with ISO 9001, SGS, CTI, ROHS certifications and comply with the GB/T 14370-2015 standard. The brand is Drilltech.



Product Name	Round Anchorage
One Set Assembly	Two pieces: anchor head, wedge
	Three pieces: anchor head, wedge, plate
	Four pieces: anchor head, wedge, plate, spiral ring
Material of anchor barrel	40Cr or S45C
Material of wedge	20CrMnTi ;20CrMn5
Type of wedge	2pcs or 3pcs
Holes	1 - 55 holes
Hardness of work anchorage (HRB)	20 - 35
Hardness of work wedge (HRC)	50 - 65
Handness of work anchorage treatrent (HRC)	50 - 100
Anchor Efficiency Cooefficient n ^a	≥ 0.95
Total Strain of Ultimate Tension ε apu (%)	≥ 2.0%
With-draw of wedge after stressing	≤ 6mm

Item	Wedges (Grips)
Features	Heat treatment
	Grade :20CrMnTi
	Use together with Anchor Head (Barrel), plate, Corrugated pipe, spiral bar, pc strand
	Two or three parts
	Weight 0.6kg
	Packing with plastic bag, in Carton
	Estándar: GB/T 14370-2015
	With-draw of wedge after stressing ≤ 6mm
Capacity	Galvanized OR Chemical Dioxide Surface Treatment (Black)
	20000 Piece/Day